

Colouring Concept

Honda's impressive CRM125R on/off-roader continues to set the pace on the streets and the trails with its high-tech design and hot performance. For 1998, its two attractive colour variations include an attention-getting purple on white two-tone and a chic and aggressive solid black which will both attract new converts to the CRM's unique brand of excitement.

Colours

- Real White
(with Adriatic Purple)
- Black



Specifications**Specifications****CRM125R (IT- & IT II-types)**

Engine		Liquid-cooled 2-stroke single
Bore × Stroke		54 × 54.5mm
Displacement		124.8cm ³
Compression Ratio		6.8 : 1
Carburettor		28mm piston valve type × 1
Max. Power Output	IT-type	25.3PS/9,500rpm (DIN) (18.6kW/9,500min ⁻¹)
	IT II-type	12.2PS/7,500rpm (DIN) (9.0kW/7,500min ⁻¹)
Max. Torque	IT-type	1.91kg-m/9,000rpm (DIN)
	IT II-type	1.24kg-m/7,000rpm (DIN) (12.2Nm/7,000min ⁻¹)
Ignition		Capacitor discharge (CDI)
Starter		Primary kick
Transmission		6-speed
Final Drive		Roller chain
Dimensions	(L×W×H)	2,210 × 830 × 1,215mm
Wheelbase		1,450mm
Seat Height		930mm
Ground Clearance		295mm
Fuel Capacity		9.5 litres (including 2.0-litre reserve)
Wheels	FrontRear	Aluminium rim/wire spoke
Tyres	Front	3.00–21 51P
	Rear	4.60–18 63P
Suspension	Front	41.7mm telescopic fork, 240mm axle travel
	Rear	Pro-Link, 285mm axle travel
Brakes	Front	240 × 4mm hydraulic disc with resin mould pads
	Rear	220 × 4mm hydraulic disc with resin mould pads
Dry Weight		118kg

All specifications are provisional and subject to change without notice.

