

**Colouring Concept**

With its futuristic racer replica design, the sporty and popular NSR125R returns to attack the streets in aggressive style.

This year the NSR rules the roadways in a racy red, white and purple tricolor design joined by a sophisticated metallic grey highlighted by black and bright flashes of metallic orange for a modern look of city-bred style.

**Colours**

- Sparkling Red  
(with Uranus Violet & Ross White)
- Heavy Grey Metallic  
(with Black & Tango Orange Metallic)



**Specifications****Specifications****NSR125R (IT- & IT II-types)**

|                   |            |   |
|-------------------|------------|---|
| Engine            |            | Liquid-cooled 2-stroke single                             |
| Bore × Stroke     |            | 54 × 54.5mm   |
| Displacement      |            | 124.8cm <sup>3</sup>                                      |
| Compression Ratio |            | 6.8 : 1   |
| Carburettor       |            | 28mm piston valve type × 1                                |
| Max. Power Output | IT-type    | 28.5PS/10,000rpm (DIN) (19.49kW/10,000min <sup>-1</sup> ) |
|                   | IT II-type | 11.4PS/7,000rpm (DIN) (8.4kW/7,000min <sup>-1</sup> )     |
| Max. Torque       | IT-type    | 1.95kg-m/9,500rpm (DIN) (19.1Nm/9,500min <sup>-1</sup> )  |
|                   | IT II-type | 1.17kg-m/7,000rpm (DIN) (11.8Nm/7,000min <sup>-1</sup> )  |
| Ignition          |            | Capacitor discharge (CDI)                                 |
| Starter           |            | Electric  |
| Transmission      |            | 6-speed   |
| Final Drive       |            | Roller chain  |
| Dimensions        | (L×W×H)    | 2,010 × 670 × 1,065mm                                     |
| Wheelbase         |            | 1,345mm   |
| Seat Height       |            | 800mm   |
| Ground Clearance  |            | 135mm   |
| Fuel Capacity     |            | 13.0 litres (including 2.8-litre reserve)                 |
| Wheels            | FrontRear  | 6-spoke cast aluminium                                    |
| Tyres             | Front      | 100/80-17 52T   |
|                   | Rear       | 130/70-17 62T   |
| Suspension        | Front      | 35mm telescopic fork, 118mm axle travel                   |
|                   | Rear       | Pro-Link, 125mm axle travel                               |
| Brakes            | Front      | 318 × 4mm hydraulic disc with resin mould pads            |
|                   | Rear       | 220 × 4mm hydraulic disc with resin mould pads            |
| Dry Weight        |            | 132kg   |

All specifications are provisional and subject to change without notice.

