



HONDA *Come ride with us.*

CBR1000F



CBR1000F - 991 - E



CBR1000F

Colouring Concept

Honda's Grand Touring CBR1000F returns for another year to provide riders with a superb balance of Super Sport performance and long-range riding comfort for both rider and passenger. Beneath its elegantly integrated total-coverage bodywork, the CBR1000F features the same easy-handling power and controlled high-speed performance—as emphasized by its innovative Dual Combined Brake System—that have made it a highly regarded sports touring companion on the roads and highways of Europe.

The CBR's two new colour variations feature the simply stated elegance of single colour tones shorn of stripes and all but the most basic graphics to project a serenely majestic image of power and prestige. In a deep, new metallic black, the CBR exudes a cool sophistication that carries it through city and country with a detached sense of style that really catches the eye. A gorgeous new solid red imbues the CBR with a lively, sport-oriented demeanour that adds a palpable rush of excitement to any ride.

Colours

- Mute Black Metallic
- Pure Red

New Features

- New colour variations.



CBR1000F - 992 - E



CBR1000F - 993 - E



CBR1000F - 994 - E

Specifications**Specifications****CBR1000F (ED & G types)**

Engine	Liquid-cooled 4-stroke 16-valve DOHC inline-4
Bore × Stroke	77 × 53.6mm
Displacement	998cm ³
Compression Ratio	10.5 : 1
Carburettors	38mm CV-type × 4
Max. Power Output	135PS/9,500rpm (DIN) (99kW/9,500min ⁻¹)
	G-type 98PS/9,000rpm (DIN) (72kW/9,000min ⁻¹)
Max. Torque	10.6kg-m/8,500rpm (DIN) (104Nm/8,500min ⁻¹)
	G-type 9kg-m/6,250rpm (DIN) (88Nm/6,250min ⁻¹)
Ignition	Computer-controlled digital transistorized with electronic advance
Starter	Electric
Transmission	6-speed
Final Drive	'O'-ring sealed chain
Dimensions	(L×W×H) 2,235 × 740 × 1,215mm
Wheelbase	1,505mm
Seat Height	780mm
Ground Clearance	140mm
Fuel Capacity	22 litres
Wheels	Front/Rear Hollow-section triple-spoke cast aluminium
Tyres	Front 120/70 VR17-270 (Radial) Rear 170/60 VR17-270 (Radial)
Suspension	Front 41mm air-assist cartridge-type fork, 130mm axle travel Rear Pro-Link with hydraulically preload-adjustable gas-charged damper, 115mm axle travel
Brakes	Front 296mm dual discs with Dual Combined three-piston calipers and sintered metal pads Rear 256mm Dual Combined three-piston caliper single disc with sintered metal pads
Dry Weight	235kg