

### Colouring Concept

The peppy little CRM50 and CRM75 'streetcrossers' return with compact proportions and super-aggressive motocrosser styling to offer a wide world of riding fun that extends from city streets to country trails. Wherever they roam, the mini CRMs deliver big-bike style, performance and all-around enjoyment in a small displacement machine.

Their two attractive colour variations for '99 include a purple and red on white tricolor that strongly emphasizes the CRMs' ties to Honda's world-renowned off-road racers, and a shiny grey and yellow on black variation that lends a touch of city-bred charm to their rugged off-road lines. Both variations feature white fenders and rear numberplate sidecovers, and black fork boots.

### Colours

- Ross White (with Adriatic Blue)
- Black (with Elephant Grey)

### New Features

- New colour variations.



**Specifications****Specifications****CRM50 (SP-type)**

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	39 × 41.4mm
Displacement	49.4cm <sup>3</sup>
Compression Ratio	7.3 : 1
Carburettor	18mm piston-valve type
Max Power Output	1.6PS/4,500rpm (DIN) (1.18kW/4,500min <sup>-1</sup> )
Max. Torque	0.28kg-m/3,500rpm (DIN) (2.7Nm/3,500min <sup>-1</sup> )
Ignition	Capacitor Discharge (CDI)
Starter	Primary kick
Transmission	6-speed
Final Drive	Roller chain
Dimensions	(L×W×H) 2,040 × 825 × 1,175mm
Wheelbase	1,355mm
Seat Height	890mm
Ground Clearance	260mm
Fuel Capacity	6.7 litres (including 1.2-litre reserve)
Wheels	Front/Rear Aluminium rim/wire spoke
Tyres	Front 2.75–21 45P Rear 3.25–18 52P
Suspension	Front 35mm hydraulic telescopic fork, 200mm axle travel Rear Pro-Link swingarm, 191mm axle travel
Brakes	Front 240mm hydraulic disc with dual-piston caliper Rear 110mm leading/trailing drum
Dry Weight	99kg

All specifications are provisional and subject to change without notice.



**Specifications****Specifications****CRM75 (SP-type)**

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	48 × 41.4mm
Displacement	74.9cm <sup>3</sup>
Compression Ratio	7.2 : 1
Carburettor	18mm piston-valve type
Max Power Output	8.4PS/8,500rpm (DIN) (6.2kW/8,500min <sup>-1</sup> )
Max. Torque	0.73kg-m/8,000rpm (DIN) (7.2Nm/8,000min <sup>-1</sup> )
Ignition	Capacitor Discharge (CDI)
Starter	Primary kick
Transmission	6-speed
Final Drive	Roller chain
Dimensions	(L×W×H) 2,040 × 835 × 1,175mm
Wheelbase	1,360mm
Seat Height	890mm
Ground Clearance	260mm
Fuel Capacity	6.7 litres (including 1.2-litre reserve)
Wheels	Front/Rear Aluminium rim/wire spoke
Tyres	Front 2.75-21 45P Rear 3.25-18 52P
Suspension	Front 35mm hydraulic telescopic fork, 200mm axle travel Rear Pro-Link swingarm, 191mm axle travel
Brakes	Front 240mm hydraulic disc with dual-piston caliper Rear 110mm leading/trailing drum
Dry Weight	99.3kg

All specifications are provisional and subject to change without notice.

