

Colouring Concept

The sporty SFX combines modern styling, comfort, convenience and exceptional riding ease to offer wide appeal to both commuters and daily users looking for an attractive and pleasurable way to get around town. Its three new colour variations place a vibrant accent on its spirited image. Led by a glamorous black variation that exudes a chic urban elegance, a bright new metallic blue and a new solid orange both catch the eye with exciting flashes of colour.

Colours

- Black
- Nexus Blue Metallic
- Ayers Rock Orange

New Features

- New colour variations.



Specifications

Specifications	SFX (IT, SP, PO, F, UK types)
Engine	Air-cooled 2-stroke single
Bore × Stroke	39 × 41.4mm
Displacement	49cm ³
Compression Ratio	7 : 1
Carburettors	16mm piston-valve type
	PO, F, UK types 14mm piston-valve type
Max Power Output	IT-type 5.39PS/ 6,750rpm (DGM) (4kW/6,750min ⁻¹) SP-type 5.39PS/ 6,750rpm (ECE) (4kW/ 6,750min ⁻¹) PO-type 5.29PS/ 6,750rpm (ISO) (3.9kW/ 6,750min ⁻¹) F-type 4.41PS/ 6,750rpm (ISO) (3.2kW/ 6,750min ⁻¹) UK-type 4.96PS/ 6,750rpm (ISO) (3.6kW/ 6,750min ⁻¹)
Max. Torque	IT-type 0.59kg-m/6,500rpm (DGM) (5.8Nm/6,500min ⁻¹) SP-type 0.59kg-m/ 6,500rpm (ECE) (5.8Nm/ 6,500min ⁻¹) PO-type 0.57kg-m/ 6,500rpm (ISO) (5.6Nm/ 6,500min ⁻¹) F-type 0.55kg-m/ 6,500rpm (ISO) (5.4Nm/ 6,500min ⁻¹) UK-type 0.50kg-m/ 6,500rpm (ISO) (4.9Nm/ 6,500min ⁻¹)
Ignition	Capacitor Discharge (CDI)
Starter	Electric/Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,723 × 636 × 1,064mm
Wheelbase	1,215mm
Seat Height	755mm
Ground Clearance	116mm
Fuel Capacity	6 litres
Wheels	Front/Rear 10 × MT2.15 cast aluminium alloy
Tyres	Front/Rear 90/90-10 (tubeless)
Suspension	Front 27mm hydraulic telescopic fork, 62.6mm axle travel Rear Unit swingarm, 70.9mm axle travel
Brakes	Front 160mm hydraulic disc with opposed dual-piston caliper and resin mould pads Rear 110mm leading/trailing drum
Dry Weight	71.2kg

All specifications are provisional and subject to change without notice.

