

SJ50 BALI/SJ100 BALI EX

Colouring Concept

With their roomy proportions and ample carrying capacity, the beautifully designed SJ50 BALI and SJ100 BALI EX set new standards for style, comfort and convenience in their class of sophisticated, city-bred scooters. For '99, the BALI twins feature two all-new colour variations: A luxurious metallic blue that calls to mind the glistening seas of summer, and a delicious metallic red that heightens their look of luxury.

Carried over from the current year are a subdued yet sophisticated metallic black and an attractive pearlescent green that draws admiring glances to the BALI's modern curves. Both models feature resin lower cowls and body parts moulded in complementary colours, with gradated stripes running the length of each side.

Colours

- Cyclone Blue Metallic
- Cassis Red Metallic (SJ50 only)
- Mute Black Metallic
- Pearl Conifer Green

New Features

- Newly designed emblems.
- New colour variations.



Specifications**Specifications****SJ50 Bali (ED-type)**

Engine	Air-cooled 2-stroke single
Bore × Stroke	39 × 41.4mm
Displacement	49cm ³
Compression Ratio	7 : 1
Carburettor	12mm piston-valve type
Max. Power Output	5.4PS/6,750rpm (DIN) (3.6kW/6,750min ⁻¹)
Max. Torque	0.50kg-m/6,500rpm (DIN) (4.9Nm/6,500min ⁻¹)
Ignition	Capacitor Discharge (CDI)
Starter	Electric/Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,765 × 710 × 1,115mm
Wheelbase	1,260mm
Seat Height	770mm
Ground Clearance	125mm
Fuel Capacity	7 litres
Wheels	Front/Rear 10 × MT2.50 cast aluminium
Tyres	Front/Rear 100/90-10 (tubeless)
Suspension	Front Trailing link with TLAD system, 64.6mm axle travel Rear Unit swingarm, 76.9mm axle travel
Brakes	Front 190mm disc with dual-piston caliper Rear 110mm leading/trailing drum
Dry Weight	86.5kg

All specifications are provisional and subject to change without notice.



Specifications**Specifications****SJ100 Bali EX (ED-type)**

Engine	Air-cooled 2-stroke single
Bore × Stroke	51 × 49.6mm
Displacement	101.3cm ³
Compression Ratio	6 : 1
Carburettor	16mm piston-valve type
Max. Power Output	8.37PS/7,000rpm (DIN) (6.15kW/7,000min ⁻¹)
Max. Torque	0.92kg-m/5,000rpm (DIN) (8.98Nm/5,000min ⁻¹)
Ignition	Capacitor Discharge (CDI)
Starter	Electric/Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,765 × 715 × 1,115mm
Wheelbase	1,260mm
Seat Height	775mm
Ground Clearance	125mm
Fuel Capacity	7 litres
Wheels	Front/Rear 10 × MT2.50 cast aluminium
Tyres	Front/Rear 100/90-10 (tubeless)
Suspension	Front Trailing link with TLAD system, 64.6mm axle travel Rear Unit swingarm, 76.9mm axle travel
Brakes	Front 190mm disc with dual-piston caliper Rear 110mm leading/trailing drum
Dry Weight	93.4kg

All specifications are provisional and subject to change without notice.

