

Colouring Concept

With the sharp, angular lines of its aggressive bodywork giving an unmistakable impression of speed even at stop, and its wide off-road style tyres and unique 'Baja racer'-style dual headlights emphasizing its sporty disposition, the lively SXR features all the ingredients for fun in the sun and an exciting time with friends on the move.

For '99, the SXR arrives on the scene in two starkly solid colour variations that extend to its 'Adventure Sports'-image front brake cover. Matte black moulded plastic trim, two-tone seat cover, buffed aluminium finish wheels and all-new graphics further set off the SXR's design with a lively flourish of exuberant style.

Colours

- Black
- Rye Yellow

New Features

- New colour variations.
- New graphics.



Specifications

Specifications	SXR (IT, PO, F, UK types)
Engine	Air-cooled 2-stroke single
Bore × Stroke	39 × 41.4mm
Displacement	49.4cm ³
Compression Ratio	7 : 1
Carburettor	12mm piston-valve type
Max. Power Output	IT-type 5.4PS/6,750rpm (DGM) (4kW/6,750min ⁻¹) PO-type 5.3PS/ 6,750rpm (ECE) (3.9kW/ 6,750min ⁻¹) F-type 4.4PS/ 6,750rpm (ISO) (3.2kW/ 6,750min ⁻¹) UK-type 5PS/ 6,750rpm (DIN) (3.6kW/ 6,750min ⁻¹)
Max. Torque	IT-type 0.59kg-m/6,500rpm (DGM) (5.8Nm/6,500min ⁻¹) PO-type 0.57kg-m/ 6,500rpm (ECE) (5.6Nm/6,500min ⁻¹) F-type 0.55kg-m/ 6,500rpm (ISO) (5.4Nm/ 6,500min ⁻¹) UK-type 0.50kg-m/ 6,500rpm (DIN) (4.9Nm/ 6,500min ⁻¹)
Ignition	Capacitor Discharge (CDI)
Starter	Electric/Kick
Transmission	V-Matic
Dimensions	(LxWxH) 1,723 × 636 × 1,064mm
Wheelbase	1,215mm
Seat Height	755mm
Ground Clearance	116mm
Fuel Capacity	6 litres
Wheels	Front/Rear 10 × MT2.15 'U'-section 6-spoke cast aluminium alloy
Tyres	Front/Rear 100/80-10 (tubeless)
Suspension	Front 27mm telescopic hydraulic fork, 62.6mm axle travel Rear Unit swingarm, 70.9mm axle travel
Brakes	Front 160mm hydraulic disc with opposed dual-piston caliper Rear 110mm leading/trailing drum
Dry Weight	72kg

All specifications are provisional and subject to change without notice.

