



NSR125R

Colouring Concept

Aggressively styled with the fast, fully faired curves of a race champion, the beautifully constructed NSR125R continues its winning ways with a high-powered combination of sharp performance and sleek Super Sport styling. Featuring an advanced aluminium chassis, quick handling suspension and a briskly responsive 2-stroke engine that puts out a sound like the GP bikes dominating the tracks of Europe, the always exciting NSR125R wins an enthusiastic following of riders and admirers on every road it takes.

For 2001, the sporty NSR receives two new colour schemes that draw their inspiration from Honda's larger displacement Super Sport champions. The first combines a bright red fuel tank and upper cowl with contrasting blue and white in an exciting Honda tricolor design. The second is a darkly glistening solid black that accentuates the NSR's advanced design with a cool, high-tech appeal.

Colours

- Sparkling Red (with Southern Blue and Ross White)
- Black

New Features

- New graphics.
- New colour variations.





NSR125R

Specifications

Specifications

NSR125R (IT-, IT-II-types) (95/1/EC-values)

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	54 × 54.5mm
Displacement	124.8cm ³
Compression Ratio	6.8 : 1
Carburettor	28mm piston-valve type
Max. Power Output	IT-type 20kW/10,000min ⁻¹ IT II-type 8.6kW/7,250min ⁻¹
Max. Torque	IT-type 19.5Nm/9,750min ⁻¹ IT II-type 11.5Nm/4,750min ⁻¹
Ignition	Capacitor Discharge (CDI)
Starter	Electric
Transmission	6-speed
Final Drive	Roller chain
Dimensions (L×W×H)	2,075 × 670 × 1,065mm
Wheelbase	1,345mm
Seat Height	800mm
Ground Clearance	135mm
Fuel Capacity	13 litres (including 2.8-litre reserve)
Wheels	Front/Rear 6-spoke cast aluminium
Tyres	Front 100/80-17 52T Rear 130/70-17 62T
Suspension	Front 35mm telescopic fork, 118mm axle travel Rear Pro-Link swingarm, 125mm axle travel
Brakes	Front 318 × 4mm hydraulic disc with dual-piston calliper and resin mould pads Rear 220 × 4mm hydraulic disc with single-piston calliper and resin mould pads
Dry Weight	132kg

All specifications are provisional and subject to change without notice.