



VT750DC Black Widow

Colouring Concept

Designed on the keywords 'longer and lower,' the new VT750DC Black Widow features a stretched-out, laid-back riding position that places the rider lower in the saddle than any large-displacement factory custom to date. Its short, drag-style handlebars and low-slung, two-tier tandem gun-fighter seat surround a muscularly tapered fuel tank to create a lean and mean riding position that gives the unmistakable feeling of sitting 'in' the machine rather than merely 'on' it. With its large, wire-spoked 19-inch front wheel and bobbed rear fender powerfully emphasising the machine's low-down design, the Black Widow's twin megaphone exhausts deliver an always-impressive sense of the V-twin engine's thundering power, for an ultimately satisfying cruising experience that lasts till daybreak and beyond.

The Black Widow cruises the boulevards in two stunning colour schemes that were specially selected to give this new cruiser a distinctive look that impressively accentuates its classic American cruiser proportions. First off is an imposing solid black that provides a sharply contrasting base for the Black Widow's brilliant chrome and metal highlights; projecting a tough, no-nonsense look of cruising cool. Next, a satiny metallic silver embodies the spare look of bare metal to give powerful expression to the new VT750DC Black Widow's classic lines and urban sophistication.

Colours

- Black
- Matte Bullet Silver Metallic





VT750DC Black Widow

Specifications

Specifications

VT750DC Black Widow (ED-type) (95/1/EC-values)

Engine	Liquid-cooled 4-stroke 6-valve SOHC 52° V-twin
Bore × Stroke	79 × 76mm
Displacement	745cm ³
Compression Ratio	9 : 1
Carburettors	34mm CV-type × 2
Max. Power Output	33kW/5,500min ⁻¹
Max. Torque	63Nm/3,000min ⁻¹
Ignition	Capacitor Discharge (CDI) with electronic advance
Starter	Electric
Transmission	5-speed
Final Drive	'O'-ring sealed chain
Dimensions (L×W×H)	2,310 × 800 × 1,070mm
Wheelbase	1,640mm
Seat Height	675mm
Ground Clearance	140mm
Fuel Capacity	13.4 litres (including 4.8-litre reserve)
Wheels	Front 19 × MT2.15 steel rim/wire spoke Rear 15 × MT3.50 steel rim/wire spoke
Tyres	Front 110/80-19 59S Rear 160/80-15M/C 74S
Suspension	Front 41mm telescopic fork, 108mm axle travel Rear Dual conventional dampers with 5-step adjustable spring preload, 80mm axle travel
Brakes	Front 296mm hydraulic disc with dual-piston calliper Rear 180mm leading/trailing drum
Dry Weight	221kg

All specifications are provisional and subject to change without notice.