

2002 NSR50 / NSR75 PRESS INFORMATION

Looking as ready for the race track as they are for the street, the aggressive little NSR50 and NSR75 pack a world of high-tech excitement into their small frames. Just like the famous Honda GP racers from which they get their name, the NSRs feature perimeter-style steel frames, racy cast aluminium wheels and 'stinger'-type exhausts. Both deliver a taste of quick, high-paced excitement that sparks the imagination of every youngster who's ever dreamed of emulating the world's greatest riders.

Colours

- **Sparkling Red**
- **Black**
- **Repsol Replica**

Specifications

NSR50 (SP-type)

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	39 × 41.4mm
Displacement	49.4cm ³
Compression Ratio	7.2 : 1
Carburettor	16mm piston-valve type
Max. Power Output	1.1kW/4,000min ⁻¹ (95/1/EC)
Max. Torque	2.9Nm/3,250min ⁻¹ (95/1/EC)
Ignition	Capacitor discharge (CDI)
Starter	Primary kick
Transmission	6-speed
Final Drive	Roller chain
Dimensions	(L×W×H) 1,905 × 665 × 1,085mm
Wheelbase	1,290mm
Seat Height	780mm
Ground Clearance	140mm
Fuel Capacity	12 litres
Wheels	Front 17 × MT2.15 cast aluminium Rear 17 × MT2.75 cast aluminium
Tyres	Front 90/80-17 48P (Tubeless) Rear 100 /80-17 52P (Tubeless)
Suspension	Front 31mm telescopic fork, 118mm axle travel Rear Pro-Link, 123mm axle travel
Brakes	Front 256 × 4mm hydraulic disc with dual-piston calliper Rear 220 × 4mm hydraulic disc with single-piston calliper
Dry Weight	98kg

All specifications are provisional and subject to change without notice.

Specifications

NSR75 (SP-type)

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	48 × 41.4mm
Displacement	74.9cm ³
Compression Ratio	7.2 : 1
Carburettor	18mm piston-valve type
Max. Power Output	9kW/9,750min ⁻¹ (DIN)
Max. Torque	2.5Nm/3,000min ⁻¹ (DIN)
Ignition	Capacitor discharge (CDI)
Starter	Primary kick
Transmission	6-speed
Final Drive	Roller chain
Dimensions	(L×W×H) 1,905 × 665 × 1,085mm
Wheelbase	1,290mm
Seat Height	775mm
Ground Clearance	140mm
Fuel Capacity	12 litres
Wheels	Front 17 × MT2.15 cast aluminium Rear 17 × MT2.75 cast aluminium
Tyres	Front 90/80-17 46P (Tubeless) Rear 100 /80-17 52P (Tubeless)
Suspension	Front 31mm telescopic fork, 130mm axle travel Rear Pro-Link, 127mm axle travel
Brakes	Front 256 × 4mm hydraulic disc with dual-piston calliper Rear 220 × 4mm hydraulic disc with single-piston calliper
Dry Weight	98kg

All specifications are provisional and subject to change without notice.