

2002

PK50 WALLAROO

PRESS INFORMATION

For fun on the beach and convenience around town, there's nothing to match the light and friendly little PK50 Wallaroo. Featuring large, 16-inch wheels for easy handling, and motorcycle-type footpegs instead of a scooter's floorboard, the Wallaroo provides carefree days of fun with friends at the seaside while making quick work of errands small or large. The Standard version Wallaroo features an easy-to-use kickstarter, and comes in two types: the Y-type 'Moped,' which can be ridden by riders 16 and older with a helmet, and the lower output S-type 'Mofa,' which can be ridden by riders 14 and older without a helmet. The Deluxe version features the handy convenience of push-button electric start and also comes in 'Moped' and 'Mofa' types.

Colours

< Standard Version >

- **Ross White**
- **Space Blue**
- **Black**

< Deluxe Version >

- **Mute Black Metallic**
- **Prime Blue Metallic**

Specifications

PK50Y WALLAROO (B-, N-, H-types)

Engine	Air-cooled 2-stroke single
Bore × Stroke	40 × 39.1mm
Displacement	49.1cm ³
Compression Ratio	6.5 : 1
Carburettor	12mm piston-valve type
Max. Power Output	B-type 1.95kW/ 5,800min ⁻¹ (95/1/EC) N-type 1.8kW/ 5,800min ⁻¹ (95/1/EC) H-type 1.18kW/ 5,000min ⁻¹ (95/1/EC)
Max. Torque	B-type 3.8Nm/3,500min ⁻¹ (95/1/EC) N-type 3.9Nm/3,500min ⁻¹ (95/1/EC) H-type 3.1Nm/3,000min ⁻¹ (95/1/EC)
Ignition	Capacitor Discharge (CDI)
Starter	Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,810 × 630 × 1,005mm
Wheelbase	1,195mm
Seat Height	790mm
Ground Clearance	130mm
Fuel Capacity	3.3 litres (including 0.8-litre reserve)
Wheels	Front 16 × MT1.50 cast aluminium Rear 16 × MT1.50 cast aluminium
Tyres	Front 2.50-16 (Tube-type) Rear 2.50-16 (Tube-type)
Suspension	Front 27.2mm grease-damper telescopic fork, 65mm axle travel Rear Unit swingarm, 72mm axle travel
Brakes	Front 95mm leading/trailing drum Rear 110mm leading/trailing drum
Dry Weight	B-type 57kg N-type 58kg H-type 56kg

All specifications are provisional and subject to change without notice.

Specifications

PK50S WALLAROO (B-type)

Engine	Air-cooled 2-stroke single
Bore × Stroke	40 × 39.1mm
Displacement	49.1cm ³
Compression Ratio	6.7 : 1
Carburettor	12mm piston-valve type
Max. Power Output	0.9kW/ 3,250min ⁻¹ (95/1/EC)
Max. Torque	3.4Nm/2,000min ⁻¹ (95/1/EC)
Ignition	Capacitor Discharge (CDI)
Starter	Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,810 × 630 × 1,005mm
Wheelbase	1,195mm
Seat Height	790mm
Ground Clearance	130mm
Fuel Capacity	3.3 litres (including 0.8-litre reserve)
Wheels	Front 16 × MT1.50 cast aluminium Rear 16 × MT1.50 cast aluminium
Tyres	Front 2.50-16 (Tube-type) Rear 2.50-16 (Tube-type)
Suspension	Front 27.2mm grease-damper telescopic fork, 65mm axle travel Rear Unit swingarm, 72mm axle travel
Brakes	Front 95mm leading/trailing drum Rear 110mm leading/trailing drum
Dry Weight	57kg

All specifications are provisional and subject to change without notice.

Specifications

PK50M WALLAROO (B-, SP-types)

Engine	Air-cooled 2-stroke single
Bore × Stroke	40 × 39.1mm
Displacement	49.1cm ³
Compression Ratio	6.5 : 1
Carburettor	12mm piston-valve type
Max. Power Output	1.95kW/ 5,800min ⁻¹ (95/1/EC)
Max. Torque	3.8Nm/3,500min ⁻¹ (95/1/EC)
Ignition	Capacitor Discharge (CDI)
Starter	Electric/Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,810 × 630 × 1,005mm
Wheelbase	1,195mm
Seat Height	790mm
Ground Clearance	130mm
Fuel Capacity	3.3 litres (including 0.8-litre reserve)
Wheels	Front/Rear 16 × MT1.50 cast aluminium
Tyres	Front/Rear 2.50-16 (Tube-type)
Suspension	Front 27.2mm grease-damper telescopic fork, 65mm axle travel Rear Unit swingarm, 72mm axle travel
Brakes	Front 95mm leading/trailing drum Rear 110mm leading/trailing drum
Dry Weight	59kg

All specifications are provisional and subject to change without notice.

Specifications

PK50SM WALLAROO (B-type)

Engine	Air-cooled 2-stroke single
Bore × Stroke	40 × 39.1mm
Displacement	49.1cm ³
Compression Ratio	6.7 : 1
Carburettor	12mm piston-valve type
Max. Power Output	0.9kW/ 3,250min ⁻¹ (95/1/EC)
Max. Torque	3.4Nm/2,000min ⁻¹ (95/1/EC)
Ignition	Capacitor Discharge (CDI)
Starter	Electric/Primary kick
Transmission	V-Matic
Dimensions	(L×W×H) 1,810 × 630 × 1,005mm
Wheelbase	1,195mm
Seat Height	790mm
Ground Clearance	130mm
Fuel Capacity	3.3 litres (including 0.8-litre reserve)
Wheels	Front 16 × MT1.50 cast aluminium Rear 16 × MT1.50 cast aluminium
Tyres	Front 2.50-16 (Tube-type) Rear 2.50-16 (Tube-type)
Suspension	Front 27.2mm grease-damper telescopic fork, 65mm axle travel Rear Unit swingarm, 72mm axle travel
Brakes	Front 95mm leading/trailing drum Rear 110mm leading/trailing drum
Dry Weight	59kg

All specifications are provisional and subject to change without notice.