

# **2002 SILVER WING PRESS INFORMATION**

Scooters have certainly come a long way in the last few years. From small and convenient two-wheelers designed only to get you from one side of town to the other to big and comfortable commuters that can carry two and a large load over long distances with luxurious ease. Honda's amazing Silver Wing takes this formula to exciting new levels of comfort and performance with a big, 600cc liquid-cooled, fuel-injected DOHC parallel-twin engine delivering a breathtaking rush of power and acceleration, and ample proportions to carry a rider and passenger in the lap of luxury all day long. With its superb wind protection, capacious under-seat storage space and the operating confidence of its Combined Brake System, the exciting Silver Wing expands the pleasures of riding and touring to the user-friendly scooter class, and opens a delightful new door to all the pleasures of the road.

## **Colours**

- **Force Silver Metallic**
- **Candy Wineberry Red**
- **Pearl Great Blue**

## **New Features**

- **New colour variations.**

## Specifications

## SILVER WING (ED-type)

Bore × Stroke	72 × 71.5mm
Displacement	582cm <sup>3</sup>
Compression Ratio	10.2 : 1
Carburation	Electronic fuel injection
Max. Power Output	37kW/7,000min <sup>-1</sup> (95/1/EC)
Max. Torque	54Nm/5,500min <sup>-1</sup> (95/1/EC)
Ignition	Computer-controlled digital transistorised with electronic advance
Starter	Electric
Transmission	V-Matic belt drive
Dimensions	(L×W×H) 2,275 × 770 × 1,430mm
Wheelbase	1,595mm
Seat Height	740mm
Ground Clearance	140mm
Fuel Capacity	16 litres (including 3.5-litre reserve)
Wheels	Front 14M/C × MT2.75 4-spoke cast aluminium Rear 13M/C × MT4.50 4-spoke cast aluminium
Tyres	Front 120/80-14M/C 58S Rear 150/70-13M/C 64S
Suspension	Front 41mm telescopic fork, 120mm axle travel Rear Dual conventional dampers with 5-step spring preload adjustment, 120mm axle travel
Brakes	Front 256 • 5mm single disc with Combined 3-piston calliper and sintered metal pads Rear 240 • 6mm dual-piston calliper disc with sintered metal pads
Dry Weight	218kg

All specifications are provisional and subject to change without notice.