

2003 CRM50 CRM75 PRESS INFORMATION

Looking like the world's most aggressive motocrossers tearing through the dirt and flying through the air, Honda's high-powered little CRM50 and CRM75 feature aggressive off-road styling and light, quick-handling performance that can take you down the street or off the beaten path with equal ease. Powered by quick-revving 2-stroke engines, their long-travel suspensions and off-road tyres provide an easy introduction to a wider world of motorcycle enjoyment, and a lots of fun wherever they roam.

Colours

- Ross White (with Adriatic Purple)
- Black (with Elephant Grey)

Specifications

CRM50 (SP-type)

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	39 × 41.4mm
Displacement	49.4cm ³
Compression Ratio	7.3 : 1
Carburettor	18mm piston-valve type
Max. Power Output	1.18kW/4,500min ⁻¹ (DIN)
Max. Torque	2.7Nm/3,500min ⁻¹ (DIN)
Ignition	Capacitor discharge (CDI)
Starter	Primary kick
Transmission	6-speed
Final Drive	Roller chain
Dimensions	(L×W×H) 2,040 × 825 × 1,175mm
Wheelbase	1,355mm
Seat Height	890mm
Ground Clearance	260mm
Fuel Capacity	6.7 litres (including 1.2-litre reserve)
Wheels	Front/Rear Aluminium rim/wire spoke
Tyres	Front 2.75-21 45P Rear 3.25-18 52P
Suspension	Front 35mm telescopic fork, 200mm axle travel Rear Pro-Link, 191mm axle travel
Brakes	Front 240mm hydraulic disc with dual-piston calliper Rear 110mm leading /trailing drum
Dry Weight	99kg

All specifications are provisional and subject to change without notice.

Specifications

CRM75 (SP-type)

Engine	Liquid-cooled 2-stroke single
Bore × Stroke	48 × 41.4mm
Displacement	74.9cm ³
Compression Ratio	7.2 : 1
Carburettor	18mm piston-valve type
Max. Power Output	6.2kW/8,500min ⁻¹ (DIN)
Max. Torque	7.2Nm/8,000min ⁻¹ (DIN)
Ignition	Capacitor discharge (CDI)
Starter	Primary kick
Transmission	6-speed
Final Drive	Roller chain
Dimensions	(L×W×H) 2,040 × 835 × 1,175mm
Wheelbase	1,360mm
Seat Height	890mm
Ground Clearance	260mm
Fuel Capacity	6.7 litres (including 1.2-litre reserve)
Wheels	Aluminium rim/wire spoke
Tyres	Front 2.75-21 45P Rear 3.25-18 52P
Suspension	Front 35mm telescopic fork, 200mm axle travel Rear Pro-Link, 191mm axle travel
Brakes	Front 240mm hydraulic disc with dual-piston calliper Rear 110mm leading /trailing drum
Dry Weight	99.3kg

All specifications are provisional and subject to change without notice.