

# **2003 GOLD WING ABS PRESS INFORMATION**

There's simply nothing on the road like the majestic Gold Wing ABS for providing the ultimate in motorcycle touring comfort and quality. Featuring a lightweight and rigid twin-spar aluminium chassis that gets its impressive surge of power from a smoothly responsive 1800cc fuel-injected flat-six engine, the Wing sets the standards for long-distance touring luxury and convenience with effortless, sporty handling and a breathtaking blast of roll-on performance the likes of which must be experienced to be believed. On top of this, its peerless Dual Combined ABS (Antilock Brake System) assures smooth, unruffled braking control over all the varying road surfaces to be encountered on your far-flung travels. With its remarkable carrying capacity, spacious accommodations for two, and such high-tech features as motor-assisted preload adjustment, push-button electric reverse, cruise control, an RDS radio entertainment system and much, much more, the Gold Wing ABS makes long-distance touring one of the most comfortable, enjoyable, and ultimately satisfying experiences to be found on wheels.

## **Colours**

- Durango Red Metallic
- Stream Silver Metallic
- Black

## **New Features**

- New colour variations

## Specifications

## GOLD WING ABS (ED-type)

Engine	Liquid-cooled 4-stroke 12-valve SOHC horizontally opposed 6-cylinder
Bore × Stroke	74 × 71mm
Displacement	1,832cm <sup>3</sup>
Compression Ratio	9.8 : 1
Carburation	PGM-FI electronic fuel injection with automatic choke
Max. Power Output	87kW/5,500min <sup>-1</sup> (95/1/EC)
Max. Torque	167Nm/4,000min <sup>-1</sup> (95/1/EC)
Ignition	Computer-controlled digital transistorised with electronic advance
Starter	Electric
Transmission	5-speed (including overdrive, plus electric reverse)
Final Drive	Enclosed shaft
Dimensions (L×W×H)	2,635 × 945 × 1,455mm
Wheelbase	1,690mm
Seat Height	740mm
Ground Clearance	125mm
Fuel Capacity	25 litres
Wheels	Front 18 × MT3.50 cast aluminium Rear 16 × MT5.00 cast aluminium
Tyres	Front 130/70-R18 (63H) Rear 180/60-R16 (74H)
Suspension	Front 45mm air-assist telescopic fork with anti-dive, 140mm stroke Rear Pro-Link Pro-Arm with electronically-controlled spring preload adjustment, 105mm axle travel
Brakes	Front 296 × 4.5mm dual hydraulic disc with Combined three-piston callipers, floating rotors and sintered metal pads Rear 316 × 11mm ventilated disc with Combined three-piston calliper and sintered metal pads
Dry Weight	363kg

All specifications are provisional and subject to change without notice.