

# **2004 JAZZ PRESS INFORMATION**

An unmistakable presence on the streets, the sportily designed Jazz really grabs attention with large proportions and fast, aggressive looks, highlighted by its sharp lines and large pair of Supersport-type multi-reflector headlights. Sharp looks isn't all the Jazz offers, though. Built for carrying two in style, its wide, plush stepped seat gives a ride that's cool and comfortable, and conceals a big carrying space that can hold a helmet, small briefcase and wide assortment of daily essentials. Its compact and powerful liquid-cooled 250cc single-cylinder engine delivers an exciting thrust of acceleration at each twist of its throttle, while its Combined Brake System provides smoothly assured balance of braking control. For work or play or just hanging out, the Jazz really calls the tune for days and nights of riding fun.

## **Colours**

- Force Silver Metallic
- Interstellar Black Metallic
- Pearl Montana Blue

<b>Specifications</b>	<b>Jazz (ED-type)</b>
Engine	Liquid-cooled 4-stroke OHC single
Displacement	249cm <sup>3</sup>
Bore x Stroke	72.7 x 60mm
Compression Ratio	10.5 : 1
Max. Power Output	14.1kW/7,000min <sup>-1</sup> (95/1/EC)
Max. Torque	20.6Nm/6,000min <sup>-1</sup> (95/1/EC)
Idling Speed	1,500min <sup>-1</sup>
Carburation	30mm CV-type carburettor (VE3BA)
Ignition System	Fully transistorised electronic
Starter	Electric
Transmission	V-Matic
Fuel Tank Capacity	12 litres
Dimensions	(LxWxH) 2,210 x 760 x 1,360mm
Wheelbase	1,545mm
Seat Height	720mm
Ground Clearance	130mm
Trail	95mm
Caster Angle	27°30'
Turning Radius	2.5m
Suspension	Front 33mm telescopic fork, 96mm axle travel Rear Dual damper unit swingarm, 120mm axle travel
Wheels	Front 13M/C x MT2.75 cast aluminium Rear 12 x MT3.50 cast aluminium
Tyres	Front 110/90-13M/C 56L Rear 130/70-12 56L

Brakes	Front 240mm hydraulic disc with Combined 3-piston calliper and sintered metal pads
	Rear 220mm hydraulic disc with single-piston calliper and sintered metal pads
Dry Weight	159kg
Kerb Weight	173kg (F: 67kg, R: 106kg)

All specifications are provisional and subject to change without notice.