

2004 SH125 SH150 PRESS INFORMATION

Looking for a scooter that's slim, sharp and easy to handle, but fast and agile enough to keep up with your busy schedule? Well meet the popular SH125—a sleek and stylish 'big wheel' scooter that may just be one of the friendliest bikes you've ever ridden. Featuring a relaxed and roomy riding position with a wide, flat floorboard for maximum legroom and comfortable commuting when dressed for work, the SH also offers ample carrying convenience both under its seat and on its spacious rear carrier. Powered by its quiet, swift and reliable liquid-cooled 4-stroke engine, the SH125 moves you down the road quickly, and with smooth, unruffled ease that sees you through the day. Its advanced Combined Brake System, with powerful front disc brake, provides confidently responsive braking control, whatever the traffic conditions, and operation couldn't be easier. For those with an eye for style and a head for deals, the SH125 makes perfect sense.

For fully licensed riders, the larger-displacement SH150 provides an extra boost in performance that makes it a perfect choice for style-conscious people on the move.

Colours

- Force Silver Metallic
- Pearl Montana Blue
- Petrol Blue Metallic
- Candy Calcutta Red
- Interstellar Black Metallic

New Features

- New colour variations.

Specifications	SH125 (ED-type)
Engine	Liquid-cooled 4-stroke SOHC single
Displacement	125cm ³
Bore x Stroke	52.4 x 57.8mm
Compression Ratio	11 : 1
Max. Power Output	10.1kW/9,000min ⁻¹ (95/1/EC)
Max. Torque	11.5Nm/7,250min ⁻¹ (95/1/EC)
Carburation	26mm VK-type carburettor
Ignition	Digital transistorised with electronic advance
Starter	Electric
Transmission	V-Matic
Final Drive	V-belt
Fuel Tank Capacity	8.3 litres
Dimensions	(LxWxH) 2,020 x 705 x 1,145mm
Wheelbase	1,335mm
Seat Height	780mm
Ground Clearance	126mm
Suspension	Front 33mm telescopic fork, 120mm axle travel Rear Dual damper unit swingarm, 70mm axle travel
Wheels	Front 16 x MT2.50 cast aluminium Rear 16 x MT2.75 cast aluminium
Tyres	Front 100/80-16 50L (Tubeless) Rear 120/80-16 60L (Tubeless)
Brakes	Front 220mm hydraulic disc with dual-piston calliper and resin mould pads Rear 130mm leading/trailing drum
Dry Weight	123.1kg

All specifications are provisional and subject to change without notice.

Specifications	SH150 (ED-type)
Engine	Liquid-cooled 4-stroke SOHC single
Displacement	153cm ³
Bore × Stroke	58 x 57.8mm
Compression Ratio	11 : 1
Max. Power Output	11.6kW/8,500min ⁻¹ (95/1/EC)
Max. Torque	14.2Nm/7,000min ⁻¹ (95/1/EC)
Carburation	26mm VK-type carburettor
Ignition	Digital transistorised with electronic advance
Starter	Electric
Transmission	V-Matic
Final Drive	V-belt
Fuel Tank Capacity	8.3 litres
Dimensions	(LxWxH) 2,020 x 705 x 1,145mm
Wheelbase	1,335mm
Seat Height	780mm
Ground Clearance	126mm
Suspension	Front 33mm telescopic fork, 120mm axle travel Rear Dual damper unit swingarm, 70mm axle travel
Wheels	Front 16 x MT2.50 cast aluminium Rear 16 x MT2.75 cast aluminium
Tyres	Front 100/80–16 50P Rear 120/80–16 60P
Brakes	Front 220mm hydraulic disc with dual-piston calliper and resin mould pads Rear 130mm leading/trailing drum
Dry Weight	123.1kg

All specifications are provisional and subject to change without notice.