

**2005
@125
@150**

PRESS INFORMATION

Get ready for some high-bandwidth excitement. The @125 really grabs attention with its modern, curvaceous lines and unique 2-in-1 headlight. Uptown, downtown, anywhere your impulse leads you, the @125 is never out of place, and so well-loved that it's always on the go. Its spacious, comfortable proportions almost make you forget how lithe and agile it can be, and its elliptical curves conceal a convenient carrying compartment right under its plushly padded seat. Hard-wired motivation comes by way of a smooth, quiet and powerful liquid-cooled 4-stroke single-cylinder engine that also features thrifty fuel economy and low emissions that everyone can appreciate, and start-ups are as easy as the push of a button. If communicative style is a big attraction in your life, let everyone know you've gone broadband aboard the @125.

For fully licensed riders, the larger-displacement @150 provides an extra boost in performance that makes it a perfect choice for those who want to maximise their transmission rates.

Colours

- Force Silver Metallic (ES version only)
- Matte Plutonium Silver Metallic (with Pearl Seashell White)
- Matte Navona Beige Metallic (with Sparkling Silver Metallic)
- Ice Blue Metallic (with Petrol Blue Metallic)
- Tropea Blue Metallic (with Force Silver Metallic)

New Features

- New colour variations.

Specifications**@125 (ED-type)****Engine**

Type	Liquid-cooled 4-stroke SOHC single
Displacement	125cm ³
Bore x Stroke	52.4 x 57.8mm
Compression Ratio	11 : 1
Max. Power Output	10.1kW/9,000min ⁻¹ (95/1/EC)
Max. Torque	11.5Nm/7,250min ⁻¹ (95/1/EC)

Fuel System

Carburation	26mm VK-type carburettor
Fuel Tank Capacity	9 litres (including 2.5-litre reserve)

Electrical System

Ignition System	Digital transistorised with electronic advance
Starter	Electric

Drivetrain

Transmission Type	V-Matic
Final Drive	V-belt

Chassis

Dimensions	(LxWxH) 1,940 x 700 x 1,170mm
Wheelbase	1,330mm
Seat Height	800mm
Ground Clearance	130mm
Dry Weight	120kg

Suspension

Type	Front 33mm telescopic fork, 88mm axle travel Rear Dual damper unit swingarm, 75mm axle travel
------	--

Wheels

Type	Front Cast aluminium Rear Cast aluminium
Rim Size	Front 13M/C x MT2.75 Rear 13M/C x MT3.50
Tyre Size	Front 110/90-13M/C 56L Rear 130/70-13M/C 57L

Specifications**@150 (ED-type)****Engine**

Type	Liquid-cooled 4-stroke SOHC single
Displacement	153cm ³
Bore x Stroke	58 x 57.8mm
Compression Ratio	11 : 1
Max. Power Output	11.6kW/8,500min ⁻¹ (95/1/EC)
Max. Torque	14.2Nm/7,000min ⁻¹ (95/1/EC)

Fuel System

Carburation	26mm VK-type carburettor
Fuel Tank Capacity	9 litres (including 2.5-litre reserve)

Electrical System

Ignition System	Digital transistorised with electronic advance
Starter	Electric

Drivetrain

Transmission Type	V-Matic
Final Drive	V-belt

Chassis

Dimensions	(LxWxH) 1,940 x 700 x 1,170mm
Wheelbase	1,330mm
Seat Height	800mm
Ground Clearance	115mm
Dry Weight	120kg

Suspension

Type	Front 33mm telescopic fork, 89mm axle travel Rear Dual damper unit swingarm, 75mm axle travel
------	--

Wheels

Type	Front Cast aluminium Rear Cast aluminium
Rim Size	Front 13M/C x MT2.75 Rear 13M/C x MT3.50
Tyre Size	Front 110/90-13M/C 56L Rear 130/70-13M/C 57L

